

## cClassId

Es un acronimo de la clase de cada control, se utiliza de manera automática para crear el `clid` en caso de que no se le asigne antes del `Create()`.

<b>cClassId</b>	<b>Clase</b>	<b>Versión</b>
fun	<a href="#">wAddFunction</a>	0.1
abw	<a href="#">wArrayBrowse</a>	0.1
bev	<a href="#">wBevel</a>	0.1
btn	<a href="#">wButton</a>	0.1
crd	<a href="#">wCard</a>	0.1
cbx	<a href="#">wCheckBox</a>	0.1
cmb	<a href="#">wComboBox</a>	0.1
dpk	<a href="#">wDatePicker</a>	0.1
edt	<a href="#">wEdit</a>	0.1
fod	<a href="#">wFileOpenImageDlg</a>	0.1
fbt	<a href="#">wFloatingBtn</a>	0.1
frm	<a href="#">wForm</a>	0.1
img	<a href="#">wImage</a>	0.1
iabw	<a href="#">wItemColBrowse</a>	0.1
icmb	<a href="#">wItemComboBox</a>	0.1
ifxi	<a href="#">wFlexItem</a>	0.1
ifbt	<a href="#">wZItemFloatBtn</a>	0.1
ilvw	<a href="#">wItemListView</a>	0.1
iplx	<a href="#">wItemParallax</a>	0.1
isnv	<a href="#">wItemSideNav</a>	0.1
isld	<a href="#">wItemSlider</a>	0.1
lbl	<a href="#">wLabel</a>	0.1
lvw	<a href="#">wListView</a>	0.1
mga	<a href="#">wMsgAlert</a>	0.1
pnl	<a href="#">wPanel</a>	0.1
plx	<a href="#">wParallax</a>	0.1
rmu	<a href="#">wRadioMenu</a>	0.1
rng	<a href="#">wRange</a>	0.1
rbr	<a href="#">wRebar</a>	0.1
sep	<a href="#">wSeparator</a>	0.1
snv	<a href="#">wSideNav</a>	0.1
sld	<a href="#">wSlider</a>	0.1
sbt	<a href="#">wSplitButton</a>	0.1
swt	<a href="#">wSwitch</a>	0.1
tpk	<a href="#">wTimePicker</a>	0.1
toa	<a href="#">wToast</a>	0.1
won	<a href="#">wWaitOn</a>	0.1
wpg	<a href="#">tWebPage</a>	0.1

From:  
<https://nefele.dev/wiki/> - **Nefele Project**

Permanent link:  
<https://nefele.dev/wiki/propiedades/cclassid?rev=1575837923>

Last update: **21/07/2020 10:50**

