

cClassId

Es un acronimo de la clase de cada control, se utiliza de manera automática para crear el [cld](#) en caso de que no se le asigne antes del `Create()`.

| cClassId | Clase | Versión |
|-----------------|-----------------------------------|----------------|
| fun | wAddFunction | 0.1 |
| abw | wArrayBrowse | 0.1 |
| bev | wBevel | 0.1 |
| btn | wButton | 0.1 |
| crd | wCard | 0.1 |
| cbx | wCheckBox | 0.1 |
| cmb | wComboBox | 0.1 |
| dpk | wDatePicker | 0.1 |
| edt | wEdit | 0.1 |
| fod | wFileOpenImageDlg | 0.1 |
| fbt | wFloatingBtn | 0.1 |
| frm | wForm | 0.1 |
| img | wImage | 0.1 |
| iabw | wItemColBrowse | 0.1 |
| icmb | wItemComboBox | 0.1 |
| ifxi | wFlexItem | 0.1 |
| ifbt | wZItemFloatBtn | 0.1 |
| ilvw | wItemListView | 0.1 |
| iplx | wItemParallax | 0.1 |
| isnv | wItemSideNav | 0.1 |
| isld | wItemSlider | 0.1 |
| lbl | wLabel | 0.1 |
| lvw | wListView | 0.1 |
| mga | wMsgAlert | 0.1 |
| pnl | wPanel | 0.1 |
| plx | wParallax | 0.1 |
| rmu | wRadioMenu | 0.1 |
| rng | wRange | 0.1 |
| rbr | wRebar | 0.1 |
| sep | wSeparator | 0.1 |
| snv | wSideNav | 0.1 |
| sld | wSlider | 0.1 |
| sbt | wSplitButton | 0.1 |
| swt | wSwitch | 0.1 |
| tpk | wTimePicker | 0.1 |
| toa | wToast | 0.1 |
| won | wWaitOn | 0.1 |
| wpg | tWebPage | 0.1 |

Controles AddOn

| cClassId | Clase | Versión |
|----------|---------------------------|---------|
| gcp | GChartPie | 0.1 |

From:

<https://nefele.dev/wiki/> - **Nefele Project**

Permanent link:

<https://nefele.dev/wiki/propiedades/cclassid?rev=1575840491>

Last update: **21/07/2020 10:50**

